

বাংলাদেশ টেলিযোগাযোগ নিয়ন্ত্রণ কমিশন


আইইবি ভবন, রমনা, ঢাকা-১০০০

CC Camera & NVR Technical Specification

| | |
|--------------------------------|---|
| Camera | Brand: Mention by tenderer |
| | Model: Mention by tenderer |
| | Origin: Taiwan, China, Malaysia, Japan, Korea . |
| | Image Sensor: 2 to 3Megapixel |
| | LAN Speed : 10/100 Based-T Ethernet |
| | ONVIF Compatible: Yes |
| | Number of Online Users: 10 |
| | Security: (1) Multiple user access levels with password (2) IP address filtering (3) Digest authentication |
| | Remote Access: (1) Internet Explorer on windows operating system (2) CMS Lite, 32CH CMS software for windows operating system (3) iOS & Android mobile devices |
| | Network compression: H.264 (Main Profile) / MJPEG |
| | Video Resolution: 1920×1080/1280×720/720×480/352×240 |
| | Frame Rate: 30fps |
| | Multiple Video Streaming: 2(H.264, MJPEG) |
| | Image Sensor: 1 / 2.7" CMOS image sensor |
| | Min Illumination: 0.1 Lux/ F1.5, 0 Lux (IR LED ON) |
| | Shutter Speed: 1/2 to 1/100 sec |
| | S/N Ratio: More than 48db (AGC Off) |
| | Lens: f3.8mm/F1.5 |
| | Viewing Angle: 77°(Horizontal)/ 45° (Vertical) / 88° (Diagonal) |
| | IR Effective Distance: Up to 25 meters |
| | IR Shift: Yes |
| | AGC: Auto |
| | IRIS Mode: AES |
| Sharpness: Yes | |
| DWDR: Yes | |
| POE: Yes (IEEE 802.3af) | |
| Weather Proof: IP66 | |
| NVR | Video Output: HDMI×2 / VGA×1 / Composite×1 |
| | Video Output Resolution: HDMI-1: Up to 3840×2160 (4k2k) HDMI-2 & VGA: Up to 1920×1080 (Full HD) |
| | Audio Output: Yes |
| | Audio Input: Yes |
| | Alarm I/O: Alarm out only |
| | HDD Capability: Eight 10TB hard disks |
| | HDD: 4TB×2 |
| | USB Ports: USB 3.0×1 / USB 2.0×2 |
| | IR Remote Control: Yes |
| | Ethernet: LAN port: 1000Mbps & Internet port: 1000Mbps |
| | Video Compression format: H.265 |

| | |
|--------------------|--|
| | Audio Compression format: G711 |
| | Record Stream: Dual |
| | Recording Mode: Manual/Event/Alarm/Schedule |
| | Pre-Alarm Recording: Yes |
| | Quick Search: Time/Event |
| | Event Notification: Push Video/Push Status/Video Mail/Message Mail |
| | Security: Yes |
| | Remote Access: Internet Explorer & CMS Lite, 32CH CMS software for windows operating system |
| | Max. Online User: 20 |
| | Multicast: Yes |
| | Seamless Recording: Yes |
| | Smart Search: Yes |
| UPS | 1200VA |
| UTP Cable | Cat 6, D-Link (Solid Copper) |
| Power Cable | BRB 23/76 |


Kollol Barua
 Deputy Asst. Director (IT)
 Bangladesh Telecommunication
 Regulatory Commission


Engr. Md. Sazder Rahman
 Assistant Director
 Administration (IT)
 Bangladesh Telecommunication
 Regulatory Commission


Engr. Mahmudur Rahman
 Senior Assistant Director
 Administration (IT)
 Bangladesh Telecommunication
 Regulatory Commission